

Lucignolo Floor

ESSENTIAL LIGHT AND PURE LINES BLEND WITH TIMELESS ALLURE

Elegant fixture for installation on a solid wall or floor surface. With soft yet focused light emission, Lucignolo aspires to be not only a functional fixture but also a decorative element, thanks to the range of painted aluminium or steel covers with elegant PVD finishes.

This treatment offer customers the chance to experiment with particularly refined colours such as gold and bronze in glossy or matt finishes.

The structure is made of die-cast aluminium, treated with electrophoresis, and coated with polyester powder. Inox model is the only suitable for floor installation.

Equipped with mid power led in two colours 2700K and 3000K.

Elegante apparecchio per l'installazione su superficie solida a parete o pavimento.

Dall'emissione luminosa morbida ma allo stesso tempo puntuale, Lucignolo aspira ad essere oltre che un apparecchio di funzione anche un elemento decorativo, grazie alla gamma di cover in alluminio verniciate o in acciaio con eleganti finiture PVD, trattamento che offre la possibilità di osare con colori particolarmente ricercati come l'oro e il bronzo in finitura lucida o opaca.


La struttura è in alluminio pressofuso, trattato con bagno di cataforesi e verniciato con polvere poliestere. Il modello in INOX è l'unico della gamma installabile a pavimento.

Equipaggiato mid power led in due colorazioni 2700K e 3000K.



Lucignolo Inox

mono emission



Available finishes:



Light Source mid power led
Supply 24V / 220-240V
Dimmer only 24V (PWM)
CRI ≥80
Electrical Class II, III
IP rating 67
Application floor
Diffuser polycarbonate diffuser


Power 24V 3Wled
220-240V 3Wled - 4,7We
Led Colour temp. 2700K/3000K



			lm		inox
2700K 3 Wled	24V	III	294	Mono emission	902232001
			lm		inox
3000K 3 Wled	24V	III	303	Mono emission	902212001
			lm		inox
2700K 4,7 Wled	220-240V	II	294	Mono emission	902231001
			lm		inox
3000K 4,7 Wled	220-240V	II	303	Mono emission	902211001

Lucignolo Inox

double emission



Available finishes:



inox


Light Source mid power led
Supply 24V / 220-240V
Dimmer only 24V (PWM)
CRI ≥80
Electrical Class II, III
IP rating 67
Application floor
Diffuser polycarbonate diffuser

Power 24V 2x3Wled
220-240V 2x3Wled - 8We
Led Colour temp. 2700K/3000K



			lm		inox
2700K 2x3 Wled	24V	III	588	Double emission	902232011
			lm		inox
3000K 2x3 Wled	24V	III	656	Double emission	902212011
			lm		inox
2700K 8 Wled	220-240V	II	588	Double emission	902231011
			lm		inox
3000K 8 Wled	220-240V	II	656	Double emission	902211011

ACCESSORIES



Recessed box
83,5x108x73mm

code **9019**
