

Talon Roof

LIGHT THE BOND BETWEEN SPACE AND INDIVIDUAL

Talon is a compact wall-mounted lighting fixture, available in single or dual emission and in two different sizes.

Made of die-cast and extruded aluminum with cataphoresis treatment and a layer of polyester powder coating, it is resistant to outdoor environments.

The tempered and silk-screened glass diffusers are bonded using a robotic system to ensure IP protection.

It features recessed optics and is equipped with a low-luminance screen to minimize glare.

The Power LED model comes with a transparent, silk-screened tempered glass diffuser, while the Mid-power LED model is provided with sandblasted glass to ensure uniform light emission.

In the 'recessed' version, the front frame is made of white-painted stainless steel, and installation is carried out using stainless steel springs for false ceilings, or alternatively with a casing for solid walls.

Talon è un apparecchio per installazione a parete compatto, disponibile con mono o bi-emissione in due diverse misure.

In alluminio pressofuso ed estruso trattamento di cataforesi e strato di vernice di polvere di poliestere resistente agli ambienti esterni, i diffusori in vetro temprato e serigrafato sono incollati tramite sistema robotico a garanzia della tenuta IP.


Caratterizzato da ottica arretrata e dotato di schermo a bassa luminanza per ridurre al massimo l'abbagliamento.

Per il modello con Power Led il diffusore è in vetro serigrafato trasparente temprato, mentre il modello Mid-power Led viene fornito con vetri sabbiati per garantire un'emissione luminosa omogenea.

Nella versione "recessed" la ghiera frontale è realizzata in acciaio INOX verniciato bianco, l'installazione avviene mediante delle molle in acciaio inox per i controsoffitti o in alternativa con casafirma per il muro pieno.



Talon Roof



Available finishes:



Light Source
Supply
Dimmer
CRI
IP rating
Electrical Class
Application
Diffuser

power led / mid power led
220-240V
upon request
≥80
IP65
I
roof
transparent glass / sandblasted

Power 220-240V 8,2Wled 10,7
4,8Wled 5,8We
Led Colour temp. 2700K / 3000K



			lm	white	sand	graphite	aluminium	corten
2700K	220- 240V	19°	756	901131122	901131123	901131124	901131125	901131128
8,2Wled		32°	760	901131132	901131133	901131134	901131135	901131138
10,7 We		65°	722	901131142	901131143	901131144	901131145	901131148

2700K	220- 240V	diffused	481	901131152	901131153	901131154	901131155	901131158
4,8 Wled								
5,8 We								

			lm	white	sand	graphite	aluminium	corten
3000K	220- 240V	19°	796	901111122	901111123	901111124	901111125	901111128
8,2Wled		32°	800	901111132	901111133	901111134	901111135	901111138
10,7 We		65°	760	901111142	901111143	901111144	901111145	901111148

3000K	220- 240V	diffused	506	901111152	901111153	901111154	901111155	901111158
4,8 Wled								
5,8 We								