

5/2 Bromham St Richmond Victoria 3121 Australia +61 3 9427 0231 sphera.com.au

Tubo louvre



Tubo is a powerful and vandal-resistant LED interior/exterior luminaire which can be suspended or surface mounted depending on your project requirements. Ideally used for public walkways, railway stations, underpasses, parks and signage,Tubo is available in 20W or 40W with clear or louver reflector. IP67 | IP69K ⊕ ♥ (€ ▲ IK10



5/2 Bromham St Richmond Victoria 3121 Australia +61 3 9427 0231 sphera.com.au

Tubo 600 Louvre

Dimensions	Ø80mm x 605mm
Finish	Clear Polycarbobate with Gold Louvre and Stainless Steel fixing
Configurations	Ceiling Mounted / Pendant
Code / Description	222B40306080CLGD / Gold Louvre Warm White 3000K 20W
Light Source	LED
Lumen Output	2300lm
CRI	80+
Lifespan	50000hrs
Rating	IP67
Voltage	220-240V



Options

Colour Temperature	4000K / 5000K
Low Volatege	Constant Voltage 24Vdc with Remote Driver

Accessories

Power Feed	Fast Pre-Wired IP Rated Connector
	C/W Mains Cable (2m Standard Length)
Dimming	Remote 24Vdc Phase-cut or Integral DALI and 1-10V Driver
IP Rating	IP69K protection for high temperature and high pressure water ingress resistance
Louvre	Aluminium Silver Finish Louvre

Additional Information

This product comes in our standard colour range however can be colour-customised to seamlessly integrate into your space. Minimum order quantities apply. For more information please contact our customer service team on +613 9427 0231 or email info@sphera.com.au



5/2 Bromham St Richmond Victoria 3121 Australia +61 3 9427 0231 sphera.com.au

Tubo 1200 Louvre

Dimensions	Ø80mm x 1205mm
Finish	Clear Polycarbobate with Gold Louvre and Stainless Steel fixing
Configurations	Ceiling Mounted / Pendant
Code / Description	222B40301280CLGD / Gold Louvre Warm White 3000K 40W
Light Source	LED
Lumen Output	4600lm
CRI	80+
Lifespan	50000hrs
Rating	IP67
Voltage	220-240V



Options

Colour Temperature	4000K / 5000K
Low Volatege	Constant Voltage 24Vdc with Remote Driver

Accessories

Power Feed	Fast Pre-Wired IP Rated Connector
	C/W Mains Cable (2m Standard Length)
Dimming	Remote 24Vdc Phase-cut or Integral DALI and 1-10V Driver
IP Rating	IP69K protection for high temperature and high pressure water ingress resistance
Louvre	Aluminium Silver Finish Louvre

Additional Information

This product comes in our standard colour range however can be colour-customised to seamlessly integrate into your space. Minimum order quantities apply. For more information please contact our customer service team on +613 9427 0231 or email info@sphera.com.au