

Alura







Alura - 13W/18W

Dimensions	125mm x 125mm x 122mm
Finish	White (WH) / Black (BK) / Custom Colour (CC)
Configurations	Ceiling Recessed
Code / Description	206B133040DIM / Warm White 3000K 13W Adjustable Dimmable 40
	206B183040DM / Warm White 3000K 18W Adjustable Dimmable 40
Light Source	LED
Lumen Output (13W)	1300lm
Lumen Output (18W)	1800lm
CRI	90+
Lifespan	50000hrs
Rating	IP20
Dimming	Phase Cut
Voltage	220-240V





Options

00K
OUK

Additional Information





Alura - 26W

Dimensions 125mm x 125mm x 129mm Finish White (WH) / Black (BK) / Custom Colour (CC) Configurations Ceiling Recessed Code / Description 206B263040DIM / Warm White 3000K 26W Adjustable Dimmable 4 Light Source LED Lumen Output 2600Im CRI 90+ Lifespan 50000hrs Rating IP20 Dimming Phase Cut Voltage 220-240V		
Configurations Ceiling Recessed Code / Description 206B263040DIM / Warm White 3000K 26W Adjustable Dimmable 4 Light Source LED Lumen Output 2600Im CRI 90+ Lifespan 50000hrs Rating IP20 Dimming Phase Cut	Dimensions	125mm x 125mm x 129mm
Code / Description 206B263040DIM / Warm White 3000K 26W Adjustable Dimmable 4 Light Source LED Lumen Output 2600Im CRI 90+ Lifespan 50000hrs Rating IP20 Dimming Phase Cut	Finish	White (WH) / Black (BK) / Custom Colour (CC)
Light Source Lumen Output 2600Im CRI 90+ Lifespan 50000hrs Rating IP20 Dimming Phase Cut	Configurations	Ceiling Recessed
Lumen Output 2600lm CRI 90+ Lifespan 50000hrs Rating IP20 Dimming Phase Cut	Code / Description	206B263040DIM / Warm White 3000K 26W Adjustable Dimmable 4
CRI 90+ Lifespan 50000hrs Rating IP20 Dimming Phase Cut	Light Source	LED
Lifespan 50000hrs Rating IP20 Dimming Phase Cut	Lumen Output	2600lm
Rating IP20 Dimming Phase Cut	CRI	90+
Dimming Phase Cut	Lifespan	50000hrs
	Rating	IP20
Voltage 220-240V	Dimming	Phase Cut
	Voltage	220-240V



115x115mn

Options

2700K / 3500K / 4000K
DALI

Additional Information





Alura - 33W

Dimensions	125mm x 125mm x 129mm
Finish	White (WH) / Black (BK) / Custom Colour (CC)
Configurations	Ceiling Recessed
Code / Description	206B333040DIM / Warm White 3000K 33W Adjustable Dimmable 40
Light Source	LED
Lumen Output	3300lm
CRI	90+
Lifespan	50000hrs
Rating	IP20
Dimming	Phase Cut
	220-240V



115x115mm

Options

2700K / 3500K / 4000K
DALI


Additional Information





Alura - Trimless 13W/18W

Dimensions	122mm x 172mm x 120mm
Finish	White (WH) / Black (BK) / Custom Colour (CC)
Configurations	Ceiling Recessed
Code / Description	206B1133040DIM / Warm White 3000K 13W Adjustable Dimmable 40
	206B1183040DIM / Warm White 3000K 18W Adjustable Dimmable 40
Light Source	LED
Lumen Output (13W)	1300lm
Lumen Output (18W)	1800lm
CRI	90+
Lifespan	50000hrs
Rating	IP20
Dimming	Phase Cut
Voltage	220-240V



Options

15° / 30°
2700K / 3500K / 4000K
DALI

Additional Information





Alura - Trimless 26W

Dimensions	122mm x 172mm x 127mm
Finish	White (WH) / Black (BK) / Custom Colour (CC)
Configurations	Ceiling Recessed
Code / Description	206B1263040DIM / Warm White 3000K 26W Adjustable Dimmable 40
Light Source	LED
Lumen Output	2600lm
CRI	90+
Lifespan	50000hrs
Rating	IP20
Dimming	Phase Cut





Options

Beam Angle	15° / 30°
Colour Temperature	2700K / 3500K / 4000K
Remote Power Supply	DALI

Additional Information





Alura - Trimless 33W

Dimensions	122mm x 172mm x 127mm
Finish	White (WH) / Black (BK) / Custom Colour (CC)
Configurations	Ceiling Recessed
Code / Description	206B1333040DIM / Warm White 3000K 33W Adjustable Dimmable 40
Light Source	LED
Lumen Output	3300lm
CRI	90+
Lifespan	50000hrs
Rating	IP20
Dimming	Phase Cut
Voltage	220-240V



115x115mm

Options

Beam Angle	15° / 30°
Colour Temperature	2700K / 3500K / 4000K
Remote Power Supply	DALI

Additional Information



Alura - 2X13W/2X18W

Dimensions	125mm x 233mm x 122mm
Finish	White (WH) / Black (BK) / Custom Colour (CC)
Configurations	Ceiling Recessed
Code / Description	206B2X133040DIM / Warm White 3000K 2X13W Adjustable Dimmable 4
	206B2X183040DIM / Warm White 3000K 2X18W Adjustable Dimmable 4
Light Source	LED
Lumen Output (13W)	2X1300lm
Lumen Output (18W)	2X1800lm
CRI	90+
Lifespan	50000hrs
Rating	IP20
Dimming	Phase Cut
Voltage	220-240V

2x13W/2x18W





▲ Supplied with double flex & plug

Options

15° / 30°
2700K / 3500K / 4000K
DALI

Additional Information



Alura - 2X26W

Dimensions	125mm x 233mm x 129mm
Finish	White (WH) / Black (BK) / Custom Colour (CC)
Configurations	Ceiling Recessed
Code / Description	206B2X263040DIM / Warm White 3000K 2X26W Adjustable Dimmable
Light Source	LED
Lumen Output	2x2600lm
CRI	90+
Lifespan	50000hrs
Rating	IP20
Dimming	Phase Cut
Voltage	220-240V





40°

▲ Supplied with double flex & plug

Options

2700K / 3500K / 4000K
DALI

Additional Information



Alura - 2X33W

Dimensions	125mm x 233mm x 129mm
Finish	White (WH) / Black (BK) / Custom Colour (CC)
Configurations	Ceiling Recessed
Code / Description	206B2X333040DIM / Warm White 3000K 2X33W Adjustable Dimmable 4
Light Source	LED
Lumen Output	2x3300lm
CRI	90+
Lifespan	50000hrs
Rating	IP20
Dimming	Phase Cut
Voltage	220-240V



115x223mm

Options

Beam Angle	15° / 30°
Colour Temperature	2700K / 3500K / 4000K
Remote Power Supply	DALI

Additional Information



Alura - Trimless 2x13W/2x18W

Dimensions	125mm x 280mm x 120mm
Finish	White (WH) / Black (BK) / Custom Colour (CC)
Configurations	Ceiling Recessed
Code / Description	206B12X133040DIM / Warm White 3000K 2x13W Adjustable Dimmable 4
	206B12X183040DIM / Warm White 3000K 2x18W Adjustable Dimmable 4
Light Source	LED
Lumen Output (13W)	2x1300lm
Lumen Output (18W)	2x1800lm
CRI	90+
Lifespan	50000hrs
Rating	IP20
Dimming	Phase Cut
	220-240V





A Supplied with double flex & plug

Options


15° / 30°
2700K / 3500K / 4000K
DALI

Additional Information



Alura - Trimless 2x26W

Dimensions	125mm x 280mm x 127mm
Finish	White (WH) / Black (BK) / Custom Colour (CC)
Configurations	Ceiling Recessed
Code / Description	206B12X263040DIM / Warm White 3000K 2x26W Adjustable Dimmable 40
Light Source	LED
Lumen Output	2x2600lm
CRI	90+
Lifespan	50000hrs
Rating	IP20
Dimming	Phase Cut





▲ Supplied with double flex & plug

Options

00K
OUK

Additional Information



Alura - Trimless 2x33W

Dimensions	125mm x 280mm x 127mm
Finish	White (WH) / Black (BK) / Custom Colour (CC)
Configurations	Ceiling Recessed
Code / Description	206B12X333040DIM / Warm White 3000K 2x33W Adjustable Dimmable 40
Light Source	LED
Lumen Output	2x3300lm
CRI	90+
Lifespan	50000hrs
Rating	IP20
Dimming	Phase Cut
Voltage	220-240V





▲ Supplied with double flex & plug

Options

Beam Angle	15° / 30°
Colour Temperature	2700K / 3500K / 4000K
Remote Power Supply	DALI

Additional Information