

Barra Inground Asymmetrical




A series of linear designed, high efficiency inground fittings, Barra is a flexible lighting system available in various sizes and wattages.

With an IP68 rating, Barra can be used in all exterior conditions, as a recessed walk over fixture or to light up surfaces and signage from below.

IP68    
IK07

Barra Inground - Asymmetrical - 549

Dimensions	549mm x 68mm x 32,5mm
Finish	Stainless Steel (SS) / Custom Colour (CC)
Configurations	Inground Recessed
Code / Description	77R18302445AS / Warm White 3000K 12x1,5W Beam 45°
Light Source	LED
Lumen Output	1020lm
CRI	80+
Lifespan	50000hrs
Rating	IP68 - IK07
Voltage	24Vdc




Options

Beam Angle	35°
Colour Temperature	4000K / 5000K

Accessories

Power Supply	Remote Driver DALI / 1-10V
Installation Box	Aluminium Recessing Box For Concrete Installation




Additional Information

This product comes in our standard colour range however can be colour-customised to seamlessly integrate into your space. Minimum order quantities apply. For more information please contact our customer service team on +61 3 9427 0231 or email info@sphera.com.au

Barra Inground - Asymmetrical - 1025

Dimensions	1025mm x 68mm x 32,5mm
Finish	Stainless Steel (SS) / Custom Colour (CC)
Configurations	Inground Recessed
Code / Description	77R36302445AS / Warm White 3000K 24x1,5W Beam 45°
Light Source	LED
Lumen Output	2055lm
CRI	80+
Lifespan	50000hrs
Rating	IP68 - IK07
Voltage	24Vdc




Options

Beam Angle	35°
Colour Temperature	4000K / 5000K

Accessories

Power Supply	Remote Driver DALI / 1-10V
Installation Box	Aluminium Recessing Box For Concrete Installation



Additional Information

This product comes in our standard colour range however can be colour-customised to seamlessly integrate into your space. Minimum order quantities apply. For more information please contact our customer service team on +61 3 9427 0231 or email info@sphera.com.au