

GORDON

design Corrado Dotti

WALL LAMP Ø12 **561.42** | **561.46**



Struttura in metallo verniciato a polveri epossidiche. Cono realizzato in metallo verniciato a polveri epossidiche o lavorato tramite trattamento galvanico con snodo rotabile a 270°. Diffusore in metacrilato.

Metal structure coated with epoxy powders. Cone made of epoxy powders coated metal or worked by galvanic treatment with 270 ° rotatable joint. Methacrylate diffuser.

DESCRIPTION and LIGHT SOURCE

561.42 wall

lampping: 1 x max 10W - E14 220/240V

dimmability: according to bulb

dimensions: Ø 12 H. 22 D. 27 cm

note: adjustable direct light 270°

CE ⚡ IP40

561.46 wall recessed

lampping: 1 x max 10W - E14 220/240V

dimmability: according to bulb

dimensions: Ø 12 H. 22 D. 25 cm

note: adjustable direct light 270°

CE ⚡ IP40



●● C2 Matt black + C2 matt black

●● C2 Matt black + C41 brushed brass

●● C2 Matt black + C44 polished gold 24KT

●● C2 Matt black + C48 black chrome

DIMENSIONS



TOOY

DISTRIBUTED BY:

Sphera

SPHERA PTY LTD
32 Lambert St Richmond
Victoria 3121 Australia

+61 3 9427 0231
sphera.com.au

SURFACE FINISHES

Verniciatura a polveri poliestere elettrostatica ad alta estetica con spessore di 80 µ cottura in forno a temperatura di 180° per 20 minuti, prova di aderenza: nessun distacco ISO 2409, nebbia salina 300 h 1 mm di penetrazione sulla croce.

Coating with high-aesthetic electrostatic polyester powder with a thickness of 80 µ cooking in the oven at a temperature of 180° for 20 minutes, proof of adherence: no detachment ISO 2409, salt spray 300 h 1 mm penetration on the cross.

CONFORMITY

La ditta Gibas s.r.l. dichiara sotto la propria responsabilità che il prodotto al quale questa dichiarazione si riferisce, è conforme, alle seguenti norme/altri documenti normativi/specifiche: EN 60598-2-1:1989 in unione con EN 60598-1:2015-01 e quindi rispondente ai requisiti essenziali delle direttive 2014/35/UE - 2011/65/UE - 2010/30/UE - 2009/125/CE