

Leo




Leo is a recessed, trimless downlight. The light source is recessed deep into the fitting creating a seamless low glare luminaire. The fixture comes complete with a recessing kit allowing the fitting to be installed and the painting and plastering to be completed with ease.

IP44    

Leo

Dimensions	88mm x 150mm x 76mm
Finish	White (WH) / Black (BK) / Custom Colour (CC)
Configurations	Ceiling Recessed
Code / Description	134B / Fixed Trimless
Rating	IP44



Cutout Size - 85mm x 85mm

Accessories


Globes	GU10 LED Globe 3000K 5W 410lm DIM
	GU10 LED Globe 4000K 5W 430lm DIM
	GU10 LED Smart Wi-Fi Globe Tunable White - Colour Changing
Controller	Wi-Fi Controller for Smart Globe (Up to 50 Globes)

Additional Information


This product comes in our standard colour range however can be colour-customised to seamlessly integrate into your space. Minimum order quantities apply. For more information please contact our customer service team on +61 3 9427 0231 or email info@sphera.com.au

LED Modules


Code / Description	LML063060LEDDIM - 3000K 6W Dimmable 36° Low Profile Module
Lumen Output	700lm
CRI	90+
Lifespan	50000hrs
Dimming	Phase-Cut
Voltage	220-240V
Options	DALI, Casambi



Code / Description	LMR063060LEDDIM - 3000K 6W Dimmable 60° Low Profile Module
Lumen Output	700lm
CRI	90+
Lifespan	50000hrs
Dimming	Phase-Cut
Voltage	220-240V
Options	DALI, Casambi



Code / Description	LMR12TW60LEDIM - 2700K 3000K 4000K 12W Dimmable 60° Module
Lumen Output	900lm
CRI	90+
Lifespan	50000hrs
Dimming	Phase-Cut
Voltage	220-240V
Options	DALI, Casambi Beam Angle 15° 24° 38°



Code / Description	LMR17TW60LEDIM - 2700K 3000K 4000K 17W Dimmable 60° Module
Lumen Output	1100lm
CRI	90+
Lifespan	50000hrs
Dimming	Phase-Cut
Voltage	220-240V
Options	DALI, Casambi Beam Angle 15° 24° 38°

